

100 Series Brass Manual Straight Valves

Features & Benefits

- · Brass straight isolation valve
- Heavy-duty brass construction
- Available in 100RS models with 1-piece rising swivel stem or 100 models with 2-piece floating swivel stem
- Full-size waterways for low-pressure loss
- Converts to automatic operation with automatic actuator
- Rated to 150 PSI maximum working pressure
- Optimal operating pressure: 30 90 PSI
- · 3-year limited warranty

- Available in:
 - 3/4" FPT inlet x 3/4", rising swivel **(100RS-075Y)**
 - 1" FPT inlet x 1", rising swivel
 - (100RS-100Y) 1-1/4" FPTD inlet x 1-1/4" rising
- 1-1/4" FPTD INIET X 1-1/4" RISING swivel **(100RS-125Y)**
- 1-1/2" FPT inlet x 1-1/2", rising swivel (**100RS-150Y**)
- 2" FPT inlet x 2", rising swivel (100RS-200Y)
 - 3/4" FPT inlet x 3/4", floating swivel **(100-75Y)**
- 1" FPT inlet x 1", floating swivel (100-100Y)

Repair & Replacement Parts

3/4" Valve Stem Rebuild Kit 1" Valve Stem Rebuild Kit 1-1/4" Valve Stem Rebuild Kit









#RK-1CPacking washer (1), seat washer (2),

Packing washer (1), seat washer (2), & red gasket (3)

#RK-2C

#RK-1C-125

1-1/2" Valve Stem

2" Valve Stem Rebuild Kit Packing O-ring (1), seat washer (2) & large O-ring (3)

Green Wheel Handle







#RK-1C-150

Packing O-ring (1), seat washer (2) & large O-ring (3)

#RK-1C-200

Packing O-ring (1), seat washer (2) & large O-ring (3))

#RK-37C

Green wheel handle compatible with 3/4" and 1" valves **ONLY**

