



Press-Fit Ball Valves

Features & Benefits

- Forged heavy construction
 - QuickTurn operation
 - Full port flow
 - cUPC and NSF/ANSI 61 Certified by IAPMO
 - For water use only
 - Press-fit connections feature easy installation without flame, works with the variety of press-fit tools
 - 3-year limited warranty
 - Unique O-ring design allows for easy identification of joints that have not been pressed
- Max pressure: 250 PSI
 - Max temperature: 203°
 - Available in:
 - 1/2" Press-fit end connections (**BV50P**)
 - 3/4" Press-fit end connections (**BV75P**)
 - 1" Press-fit end connections (**BV100P**)
 - 1-1/4" Press-fit end connections (**BV125P**)
 - 1-1/2" Press-fit end connections (**BV150P**)
 - 2" Press-fit end connections (**BV200P**)





BVP Series
Press-Fit Ball Valves

Materials & Dimensions

Component	Material
Valve Body	Lead-Free DZR Brass
Bonnet	Lead-Free DZR Brass
Ball	Lead Free DZR Brass, Chrome Plated
Seal	PTFE
Stem	Lead-Free Brass*
O-rings	EPDM
Washer	Stainless Steel
Stem	Brass
Lock Nut	Stainless Steel
Sleeve	POM
Handle	Steel - Dacromet Plated

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
BV50P	5.25	1.25	2	0.4
BV75P	6	1.5	3	0.73
BV100P	6.125	1.91	3.25	1.01
BV125P	6.75	2.25	4	1.5
BV150P	8	2.75	4.5	2.18
BV200P	8.25	3.375	5.25	3.75



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause, cancer and reproductive harm. For more information, go to www.P65Warnings.ca.gov