



PU61DP-C



LMG-B



RO-100-B

Plastic Impulse & Rotor Sprinklers

Features & Benefits

- Impact resistant ABS construction
 - Adjustable to full or partial circle coverage
 - **PU61DP-C** standard nozzle 5/32" - 25° angle. Diffuser pin breaks up jetstream for a closer distribution. Anti-backsplash arm reduces side-water waste
 - **LMG-B** 1/2" bottom and side inlets (see back for more information)
 - **RO-100-B** 4" pop-up height. 1/2" and 3/4" bottom inlet. Includes eight (8) interchangeable nozzles and adjustment tools (see back for flow rates)
 - Optimal pressure: 25 -65 PSI
 - Available in boxed (-B) or carded (-C) for retail
 - **3-year limited warranty**
- Available in:
 - Plastic pop-up impulse sprinkler boxed 65201 (**LMG-B**)
 - Plastic impulse s1/2" MPT precision arm carded (**PU61DP-C**)
 - Plastic gear-driven rotor pop-up sprinkler, individually boxed (**RO-100-B**)



Model LMG-B	Pressure PSI	Flow GPM	RADIUS Feet
Red low gallonage nozzle	25	2.2 / 3.0	29 / 35
	30	2.4 / 3.3	31 / 38
	35	2.6 / 3.6	33 / 41
Standard green nozzle	35	2.6 / 3.6	33 / 41
	40	2.8 / 3.8	35 / 43
	45	3.0 / 4.0	37 / 43

Model PU61DP-C	Pressure PSI	Flow GPM	RADIUS Feet
	25	3.0	35'
	30	3.3	36'
	35	3.4	37'
	40	3.6	38'
	45	4.0	38'

Model RO-100-B Nozzle #	Pressure PSI	Flow GPM	RADIUS Feet
No. 1	40	1.0	35
	50	1.4	38
	60	1.5	38
No. 2	40	2.5	39
	50	3.0	40
	60	3.1	41
No. 2.5 (installed)	40	2.3	39
	50	3.2	40
	60	3.5	41
No. 3	40	3.3	42
	50	3.6	45
	60	4.2	46
No. 4	40	4.5	45
	50	5.4	47
	60	5.8	52
No. 6	40	6.2	49
	50	7.0	51
	60	7.9	54
No. 8	40	8.0	47
	50	8.9	51
	60	9.6	55

