


Brass Impact Sprinklers

300-A-16-14

S201-2-10-06

S201-2-12-08

U61DP-C



Brass full circle impact sprinkler, 1" MPT, double nozzle, diffuser pin (1/4" x 7/32")

PSI	GPM	RAD	■ IN/HR	▲ IN/HR
60	24.7	63'	0.6	0.5
70	26.8	65'	0.5	0.4
80	28.8	67'	0.5	0.4

Brass full circle impact sprinkler - 3/4" male/sure seal, double nozzle (5/32" x 3/32")

PSI	GPM	RAD	■ IN/HR	▲ IN/HR
60	10.6	50'	0.4	0.3
70	11.5	51'	0.4	0.3
80	12.4	52'	0.4	0.3

Brass full circle impulse - 3/4" male/sure seal, double nozzle (3/16" x 1/8")

PSI	GPM	RAD	■ IN/HR	▲ IN/HR
60	10.6	50'	0.4	0.3
70	11.5	51'	0.4	0.3
80	12.4	52'	0.4	0.3

Brass impulse sprinkler 1/2" MPT with precision spray arm ("C" carded for retail)

PSI	GPM	RAD	■ IN/HR	▲ IN/HR
40	4.55	43'	0.4	0.4
50	5.15	47'	0.5	0.4
60	5.65	48'	0.5	0.4

NOTE: Square spacing ■ is calculated at 50% diameter of throw. Triangle spacing ▲ is calculated at 60% diameter of throw. Pressure (PSI) is measured at the nozzle. Flow rates shown are maximum. Inserts are adjustable for less GPM flow. Assumes ideal conditions.