



Lead-Free Boiler Drains

Arrowhead Brass boiler drains are made of lead-free dezincification resistant brass and are available in a variety of connection types and options. Arrowhead Brass lead-free boiler drains are certified to NSF/ANSI 61 and cUPC listed by IAMPO.

Features and Specifications

- Forged heavy construction lead-free dezincification resistant brass. NSF/ANSI 61 certified by IAPMO.
- Multi-purpose supply and drain valves for use in low pressure water systems.
- “-QT” models available with QuickTurn® 1/4 ball-valve operation.
- Maximum pressure: 125 PSI
- 3-year limited warranty.

Models

BD50C	Boiler Drain 1/2" Copper Compressions x 3/4" MHT
BD50F	Boiler Drain 1/2" Female Iron Pipe Thread x 3/4" MHT
BD50M	Boiler Drain 1/2" Male Iron Pipe Thread x 3/4" MHT
BD50X	Boiler Drain 1/2" PEX Crimp (F1807) x 3/4" MHT with Nylon Lock Nut.
BD75F	Boiler Drain 3/4" Female Iron Pipe Thread x 3/4" MHT
BD75M	Boiler Drain 3/4" Male Iron Pipe Thread x 3/4" MHT
BD50F-QT	Boiler Drain 1/2" Female Iron Pipe Thread x 3/4" MHT - QuickTurn
BD50M-QT	Boiler Drain 1/2" Male Iron Pipe Thread x 3/4" MHT - QuickTurn
BD75F-QT	Boiler Drain 3/4" Female Iron Pipe Thread x 3/4" MHT - QuickTurn
BD75M-QT	Boiler Drain 3/4" Male Iron Pipe Thread x 3/4" MHT - QuickTurn

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
BD50C	2.5	2	3.875	0.56
BD50F	2.5	2	3.375	0.48
BD50M	2.5	2	3.5	0.49
BD50X	2.5	2	4.75	0.53
BD75F	2.5	2	3.5	0.53
BD75M	2.5	2	4	0.55
BD50F-QT	2.375	1	2.375	0.27
BD50M-QT	2.375	1	2.5	0.28
BD75F-QT	2.375	1.25	2.375	0.3
BD75M-QT	2.375	1	2.5	0.3

