



CPVC Supply Stops

Arrowhead Brass & Plumbing angle and straight supply stops are made of lead-free dezincification resistant brass and are available in a variety of connection types. The CPVC Supply Stop Valves, with 3/8-inch or 1/4-inch compression outlets, feature a polished chrome finish and QuickTurn® operation. Arrowhead Brass & Plumbing Supply Stops are certified to NSF/ANSI 61 and cUPC listed by IAMPO.



Models

AS50P25C Angle Supply Stop, 1/2" CPVC x 1/4" OD Compression

AS50P37C Angle Supply Stop, 1/2" CPVC x 3/8" OD Compression

SS50P37C Straight Supply Stop, 1/2" CPVC x 3/8" OD Compression

Features and Specifications

- Forged lead-free brass construction, chrome plated body. NSF/ANSI 61 certified by IAPMO.
- Angle and straight models with 1/2-inch CPVC (glue on) inlet. QuickTurn® 1/4 ball-valve operation.
- 3-year limited warranty.

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
AS50P25C	2	1	2.875	0.26
AS50P37C	2.125	1	2.875	0.26
SS50P37C	3.1	1	1.5	0.25

Component	Material
Valve Body	Lead-Free DZR Brass, Chrome Plated
Seal	PTFE
Ball	Lead-Free DZR Brass, Chrome Plated
O-Ring	EPDM
Stem	Lead-Free DZR Brass, Chrome Plated
Handle	ABS
Lock Nut	Stainless Steel SS304
Bonnet	Lead-Free DZR Brass, Chrome Plated
Ferrule	Brass, Chrome Plated
Nut	Brass, Chrome Plated

