



## Lead-Free Ball Valves Press-Fit BVP Series



Arrowhead Brass & Plumbing Ball valves are made of Lead-Free dezincification resistant brass and are available in a variety of connection types. The BVP series Press-Fit end connection ball valves, available in 1/2-inch through 2-inch sizes, feature full-port flow and QuickTurn® operation. Arrowhead Brass & Plumbing Ball Valves are certified and listed by IAMPO to all relevant standards.

### Features and Specifications

- Full port, forged lead-free brass construction.
- cUPC and NSF/ANSI 61 certified by IAPMO.
- Unique O-ring design that allows water leaks for installers to identify any joints that have not been pressed.
- Press-fit connections feature easy installation without flame, works with a variety of press-fit tools.
- 3-year limited warranty.
- Maximum pressure: 250 PSI.
- Maximum temperature: 203° (F).

Models

<b>BV50P</b>	1/2" Press-Fit Connections
<b>BV75P</b>	3/4" Press-Fit Connections
<b>BV100P</b>	1" Press-Fit Connections
<b>BV125P</b>	1-1/4" Press-Fit Connections
<b>BV150P</b>	1-1/2" Press-Fit Connections
<b>BV200P</b>	2" Press-Fit Connections

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
BV50P	5.25	1.25	2	0.4
BV75P	6	1.5	3	0.73
BV100P	6.125	1.91	3.25	1.01
BV125P	6.75	2.25	4	1.5
BV150P	8	2.75	4.5	2.18
BV200P	8.25	3.375	5.25	3.75

Component	Material
Valve Body	Lead-Free DZR Brass
Bonnet	Lead-Free DZR Brass
Ball	Lead Free DZR Brass, Chrome Plated
Seal	PTFE
Stem	Lead-Free Brass*
O-rings	EPDM
Washer	Stainless Steel
Stem	Brass
Lock Nut	Stainless Steel
Sleeve	POM
Handle	Steel - Dacromet Plated

