



Standard Frost-Free Sillcocks

Arrowhead Brass & Plumbing Frost-Free Sillcocks are made of Lead-Free dezincification resistant brass and are available in a variety of lengths and connection types. Arrowhead Brass & Plumbing Frost-Free Sillcocks are certified and listed by IAPMO to ASSE 1019 and NSF/ANSI 61.



Models

FF50M**	Frost-Free Sillcock 1/2" MIP & Sweat x 3/4" MHT
FF75M**	Frost-Free Sillcock 3/4" MIP & 1/2" FIP x 3/4" MHT
FF50RG**	Frost-Free Sillcock 1/2" REDIGRIP Push-Fit x 3/4" MHT

**** = Hydrant length:**

- 04 - 4" insertion depth
- 06 - 6" insertion depth
- 08 - 8" insertion depth
- 10 - 10" insertion depth
- 12 - 12" insertion depth
- 14 - 14" insertion depth

Features and Specifications

- Full port, forged lead-free brass construction.
- Certified to NSF/ANSI 61 and ASSE 1019.
- Frost-Free sillcocks provide a non-freezing water supply when installed with a downward angle toward the hose outlet and the hose or other attachments are removed.
- 2 base models:
 - FF50M series with 1/2-inch male iron pipe thread and 1/2-inch copper sweat inlet,
 - FF75M with 3/4-inch male iron pipe and 1/2-inch female iron pipe thread inlet.
 - FF50RG series with 1/2-inch REDIGRIP Push-Fit inlet connection.
- 3-year limited warranty.
- Maximum pressure: 125 PSI.
- Maximum temperature: 140° (F).
- Standard Frost-Free Sillcocks do not include anti-siphon back-flow prevention. For ASSE 1019 anti-siphon certified frost-free sillcocks, please see the FA series by Champion Plumbing.

