



Lead-Free Stop & Waste Valves



Champion Plumbing Stop and Stop & Waste Valves are made of lead-free dezincification resistant brass and are available in 1/2-inch and 3/4-inch sizes with threaded, copper sweat or copper compression connections. Champion Plumbing lead free stop valves are certified to NSF/ANSI 61 and cUPC listed by IAMPO.

Features and Specifications

- Forged heavy construction lead-free dezincification resistant brass. NSF/ANSI 61 certified by IAPMO.
- Multi-purpose in-line shut-off valves for use in low pressure water systems.
- “-W” models feature waste for draining outlet water line.
- Maximum pressure: 125 PSI
- 3-year limited warranty.

Models

SV50C	Stop Valve 1/2 Copper Compression Connections
SV50C-W	Stop & Waste Valve 1/2 Copper Compression Connections
SV50F	Stop Valve 1/2 Female Pipe Thread Connections
SV50F-W	Stop & Waste Valve 1/2 Female Pipe Thread Connections
SV50S	Stop Valve 1/2 Copper Sweat Connections
SV50S-W	Stop & Waste Valve 1/2 Copper Sweat Connections
SV75C	Stop Valve 3/4 Copper Compression Connections
SV75C-W	Stop & Waste Valve 3/4 Copper Compression Connections
SV75F	Stop Valve 3/4 Female Pipe Thread Connections
SV75F-W	Stop & Waste Valve 3/4 Female Pipe Thread Connections
SV75S	Stop Valve 3/4 Copper Sweat Connections
SV75S-W	Stop & Waste Valve 3/4 Copper Sweat Connections

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
SV50C	2.875	2	3.3	0.48
SV50C-W	2.875	2	3.3	0.61
SV50F	1.9	2	3.3	0.46
SV50F-W	1.9	2	3.3	0.57
SV50S	2	2	3.3	0.45
SV50S-W	2	2	3.3	0.48
SV75C	3.125	2	3.42	0.79
SV75C-W	3.125	2	3.42	0.82
SV75F	2.17	2	3.42	0.64
SV75F-W	2.17	2	3.42	0.66
SV75S	2.335	2	3.42	0.59
SV75S-W	2.335	2	3.42	0.62

