

AS Series Angle Supply Stops



Cold Expansion PEX



Copper Sweat



FIP Thread



Push-Fitting



PEX



Compression



CPVC



Crimp PEX

Angle Supply Stops

Features & Benefits

- Forged lead-free brass body
- Chrome-plated
- NSF/ANSI 61 certified by IAPMO
- QuickTurn® 1/4 ball-valve operation
- Connection types include: push-fit, crimp-style PEX (ASTM F1807), copper sweat, compression, female iron pipe thread, cold expansion PEX (ASTM F1960), and CPVC (glue on)
- **3-year limited warranty**
- Available in:
 - 1/2" crimp PEX x 1/4" OD compression (**AS50X25C**)
 - 3/4" crimp PEX x 3/8" OD compression (**AS50X37C**)
 - 1/2" push-fitting x 1/4" OD compression (**AS50R25C**)

- 1/2" push-fitting x 3/8" OD compression (**AS50R37C**)
- 1/2" copper sweat x 1/4" OD compression (**AS50S25C**)
- 1/2" copper sweat x 3/8" OD compression (**AS50S37C**)
- 5/8" OD compression x 1/4" OD compression (**AS50C25C**)
- 5/8" OD compression x 3/8" OD compression (**AS50C37C**)
- 1/2" FIP x 1/4" OD compression (**AS50F25C**)
- 1/2" FIP x 3/8" OD compression (**AS50F37C**)
- 1/2" cold expansion PEX x 1/4" OD compression (**AS50U25C**)
- 1/2" cold expansion PEX x 3/8" OD compression (**AS50U37C**)



- 1/2" CPVC x 1/4" OD compression (**AS50P25C**)
- 1/2" CPVC x 3/8" OD compression (**AS50P37C**)



Materials & Dimensions

Component	Material
Valve Body	Lead-Free DZR Brass, Chrome Plated
Seal	PTFE
Ball	Lead-Free DZR Brass, Chrome Plated
O-Ring	EPDM
Stem	Lead-Free DZR Brass, Chrome Plated
Handle	ABS
Lock Nut	Stainless Steel SS304
Bonnet	Lead-Free DZR Brass, Chrome Plated
Ferrule	Brass, Chrome Plated
Nut	Brass, Chrome Plated

* Lead Free is defined as less than 0.25% lead content, certified by IAPMO to NSF/ANSI 372

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
AS50F25C	2	1	1.93	0.2
AS50F37C	2.125	1	1.93	0.2
AS50C25C	2	1	2.125	0.2
AS50C37C	2.125	1	2.125	0.2
AS50S25C	2	1	1.9	0.18
AS50S37C	2.125	1	1.9	0.18
AS50R25C	2	1.125	2.25	0.22
AS50R37C	2.125	1.125	2.25	0.22
AS50X25C	2	1	2	0.17
AS50X37C	2.125	1	2	0.17
AS50U25C	2	1	2.19	0.19
AS50U37C	2.125	1	2.19	0.19
AS50P25C	2	1	2.875	0.26
AS50P37C	2.125	1	2.875	0.26



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause, cancer and reproductive harm. For more information, go to www.P65Warnings.ca.gov