



## Ball Valve Hose Bibs

### Features & Benefits

- Heavy duty lead-free brass construction
- Certified to NSF/ANSI 372
- Bi-directional QuickTurn operation
- Chrome-plated brass ball and PTFE seals
- Imported, made in China
- ADA Compliant
- Maximum pressure: 125 PSI
- Maximum temperature: 180° F
- Flow rate: 8-9 GPM at 50 PSI
- 3-year limited warranty
- Available in:
  - No-Kink 1/2" MIP x 3/4" MHT (**251BVLF**) & 3/4" MIP x 3/4" MHT (**351BVLF**)
  - No-Kink 1/2" Sweat x 3/4" MHT (**252BVLF**) & 3/4" Sweat x 3/4" MHT (**352BVLF**)
  - No-Kink 1/2" FIP x 3/4" MHT (**253BVLF**) & 3/4" FIP x 3/4" MHT (**353BVLF**)
  - Solid-flange sillcock 1/2" FIP x 3/4" MHT (**255BVLF**) & 3/4" FIP x 3/4" MHT (**355BVLF**)





## Dimensions

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
251BVLF	5.25	1.25	2.25	0.7
252BVLF	5.25	1.25	2.25	0.7
253BVLF	5.25	1.25	2.25	0.62
351BVLF	5.25	1.25	2.25	0.73
353BVLF	5.25	1.25	2.25	0.066
255BVLF	5.25	1.25	2.25	0.78
355BVLF	5.25	1.25	2.25	0.076



**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause, cancer and reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)