



Push-Fit Ball Valves

Features & Benefits

- Forged heavy construction
 - QuickTurn® operation
 - Full port flow
 - Push-fit ends comply with ASSE 1061
 - For water use only
 - Easily connects to copper, PEX, and CPVC
 - 3-year limited warranty
 - Max pressure: 232 PSI
 - Max temperature: 203°
- Available in:
 - 1/2" Push-fit end connections (**BV50R**)
 - 3/4" Push-fit end connections (**BV75R**)
 - 1" Push-fit end connections (**BV100R**)





Materials & Dimensions

Component	Material
Valve Body	Lead-Free DZR Brass
Seal	PTFE
Ball	Lead-Free DZR Brass, Chrome Plated
Bonnet	Lead-Free DZR Brass
Stem	Lead-Free Brass*
O-ring	EPDM
Packing	PTFE
Gland Nut	Brass
Handle	Steel
Washer	Stainless Steel
Lock Nut	Brass
Sleeve	POM
Grip Ring	Stainless Steel
Guard	POM
Liner	PSF

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
BV50R	5	1.25	2.5	0.48
BV75R	5.5	1.5	2.5	0.7
BV100R	6	1.375	3.375	1.28



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause, cancer and reproductive harm. For more information, go to www.P65Warnings.ca.gov