


300-A-16-14



S201-2-10-6



S201-2-12-08



U61DP-C

Brass Impulse Sprinklers

Features & Benefits

- Heavy-duty brass body
 - Adjustable to full or partial circle coverage
 - Optimal pressure: 25 -65 PSI
 - Available in boxed (-**B**) or carded (-**C**) for retail
 - **3-year limited warranty**
- Available in:
 - Brass full-circle impulse sprinkler 1" MPT, double nozzle, diffuser pin - 1/4" x 7/32" (**300-A-16-14**)
 - Brass full-circle impulse sprinkler - 3/4" male/sure seal, double nozzle - 5/32" x 3/32" (**S201-2-10-06**)
 - Brass full-circle impulse sprinkler - 3/4" male / sure seal, double nozzle - 3/16" x 1/8" (**S201-2-12-08**)
 - Brass full-circle impulse sprinkler - 1/2" MPT with precision spray arm ("C" carded for retail) (**U61DP-C**)

Model	PSI	GPM	RAD	■ IN/HR	▲ IN/HR
300-A-16-14	60	24.7	63'	0.6	0.5
	70	26.8	65'	0.5	0.4
	80	28.8	67'	0.5	0.4
S201-2-10-06	60	10.6	50'	0.4	0.3
	70	11.5	51'	0.4	0.3
	80	12.4	52'	0.4	0.3
S201-2-12-08	60	10.6	50'	0.4	0.3
	70	11.5	51'	0.4	0.3
	80	12.4	52'	0.4	0.3
U61DP-C	40	4.55	43'	0.4	0.4
	50	5.15	47'	0.5	0.4
	60	5.65	48'	0.5	0.4

NOTE: Square spacing ■ is calculated at 50% diameter of throw. Triangle spacing ▲ is calculated at 60% diameter of throw. Pressure (PSI) is measured at the nozzle. Flow rates shown are maximum. Inserts are adjustable for less GPM flow. Assumes ideal conditions.

