



Lead-Free Boiler Drains

Features & Benefits

- Forged heavy construction lead-free dezincification resistant brass. NSF/ANSI 61 certified Lead Free by IAPMO.
 - Multi-purpose supply and drain valves for use in low-pressure water systems
 - "-QT" models available with QuickTurn® 1/4 ball valve operation
 - Maximum pressure: 125 PSI
 - 3-year limited warranty.
- Available in:
 - 1/2" & 3/4" Female Iron Pipe Threads - FIP (**BD50F & BD75F**)
 - 1/2" & 3/4" Male Iron Pipe Threads - MIP (**BD50M & BD75M**)
 - 1/2" Copper Compression (**BD50C**)
 - 1/2" PEX Crimp (**BD50X**)
 - 1/2" & 3/4" Female Iron Pipe Threads - FIP with QuickTurn® (**BD50F-QT & BD75F-QT**)
 - 1/2" & 3/4" Male Iron Pipe Threads - MIP with QuickTurn® (**BD50M-QT & BD75M-QT**)





Dimensions

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
BD50C	2.5	2	3.875	0.56
BD50F	2.5	2	3.375	0.48
BD50M	2.5	2	3.5	0.49
BD50X	2.5	2	4.75	0.53
BD75F	2.5	2	3.5	0.53
BD75M	2.5	2	4	0.55
BD50F-QT	2.375	1	2.375	0.27
BD50M-QT	2.375	1	2.5	0.28
BD75F-QT	2.375	1.25	2.375	0.3
BD75M-QT	2.375	1	2.5	0.3

* Lead Free is defined as less than 0.25% lead content, certified by IAPMO to NSF/ANSI 372

Models

#BD50C



BD50C

1/2" copper compression x 3/4" MHT

#BD50F



BD50F

1/2" FIP thread x 3/4" MHT

#BD50M



#BD50M

1/2" MIP thread x 3/4" MHT

#BD50X



BD50X

1/2" PEX crimp (F1807) x 3/4" MHT with nylon lock nut

#BD75F



BD75F

3/4" FIP thread x 3/4" MHT

#BD75M



BD75M

3/4" MIP thread x 3/4" MHT

#BD50F-QT



#BD50F-QT

1/2" FIP thread x 3/4" MHT - QuickTurn®

#BD50M-QT



BD50M-QT

1/2" MIP thread x 3/4" MHT - QuickTurn®

#BD75F-QT



#BD75F-QT

3/4" FIP thread x 3/4" MHT - QuickTurn®

#BD75M-QT



BD75M-QT

3/4" MIP thread x 3/4" MHT - QuickTurn®



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause, cancer and reproductive harm. For more information, go to www.P65Warnings.ca.gov