



SC Series Sillcocks

Features & Benefits

- Forged heavy-duty lead-free dezincification resistant brass
- NSF/ANSI 372 certified by IAPMO
- Multi-purpose supply valves with wall flange for use in low-pressure water systems
- "-QT" models are available with QuickTurn® 1/4 ball valve operation
- Maximum pressure: 125 PSI
- **3-year limited warranty**

- Available in:
 - 1/2" FIP thread inlet (**SC50F**)
 - 1/2" FIP thread inlet - QuickTurn® (**SC50F-QT**)
 - 1/2" Copper sweat inlet (**SC50S**)
 - 1/2" Copper sweat inlet - QuickTurn® (**SC50S-QT**)
 - 3/4" FIP thread inlet (**SC75F**)
 - 3/4" FIP thread inlet - QuickTurn® (**SC75F-QT**)





Dimensions

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)
SC50F	2.25	2	4	0.57
SC50F-QT	2.25	1.625	2.75	0.34
SC50S	2.375	2	4	0.61
SC50S-QT	2.375	1.625	2.75	0.35
SC75F	2.25	2	4	0.61
SC75F-QT	2.25	1.625	2.75	0.33

* Lead Free is defined as less than 0.25% lead content, certified by IAPMO to NSF/ANSI 372



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause, cancer and reproductive harm. For more information, go to www.P65Warnings.ca.gov